

zipato®



# ZIPATILE2

ALL-IN-ONE SMART HOME SERVER



## INTERCOM

- SIP server client
- Door phone control
- Conference calls
- Video calls
- Dual-network IP connectivity
- Remote control with smartphone



## SECURITY ALARM

- Presence sensor
- Noise sensor
- Shock sensor
- Touch keypad
- Alarm siren multi-sound
- Photo and video messages
- 24/7 central monitoring
- Remote control with smartphone



## HOME AUTOMATION

- Remote control with smartphone
- Rule creator online
- Scene manager
- Room manager
- Z-Wave, ZigBee, Nest, Philips Hue, Sonos, Bluetooth, Homekit...



## THERMOSTAT

- Gas/floor heating
- Temperature meter
- Exterior temperature meter
- Air condition control
- Remote control with smartphone



## WALL PANEL

- Room temperature
- Room illuminance
- Room humidity
- Weather forecast
- Sticky notes
- News stream
- Photo frame
- Email, Skype, browser
- Multimedia control
- Scene controller 3 buttons



## ELDERLY CARE

- Motion sensor
- Noise detector
- Automatic check calls
- Panic button with auto call
- Sound reminders
- Video and voice calls



## IP CAMERA

- Live video stream H.264
- Motion and scheduled recordings
- Remote control with smartphone





# ZIPATILE2

## TECHNICAL SPECIFICATIONS

### SYSTEM

Quad-Core Cortex ARM CPU  
Mali400 MP2 GPU  
2GB RAM  
8GB FLASH  
Android 8.1 Oreo

### NETWORK

Ethernet (built-in)  
Wi-Fi 802.11 b/g/n  
Bluetooth 4.x  
Z-Wave+ (500 series, optional)  
ZigBee HA (optional)  
EnOcean (optional)  
433 MHz (optional)  
ULE (optional)  
3G/4G (cloud connection backup, optional)  
DECT

### SENSORS

Noise  
Light  
Humidity  
Temperature  
Motion  
Shock

### POWER

Power input: 5VDC  
Power supply input: 100-240VAC, 50/60Hz  
Power usage: <2W (Idle), 7W (Max.)  
Backup battery: Li-Ion 3.7V 3500mAh  
POE (Power Over Ethernet, optional)  
HVAC power (using C wire, optional)

### INPUT/OUTPUT

Touch sensitive 8" screen, 800x1280px  
3 programmable scene buttons  
4 dry outputs 230VAC, 1A (60 W max)  
1 dry input 230VAC  
HVAC interface (support for 2-5 wire thermostat installations, HVAC version only)  
Security camera with privacy switch  
Multi-sound alarm siren, 100 dB @ 10cm  
Stereo speakers 2x1W  
Microphone

### ACCESSORIES

In-Wall power supply  
Wall socket adapter  
Wall mounting kit  
VESAs mounting kit

### PHYSICAL DIMENSION

7.9 (W) x 7.9 (H) x 0.6 (D) inches  
200 (W) x 200 (H) x 15 (D) millimeters

### ENVIRONMENTAL

Operating temperature: 0°C to 40°C  
(32°F to 104°F)  
Storage temperature: -25°C to 70°C  
(-13°F to 158°F)  
Humidity: 5% to 95% non-condensing

### REGULATION

Safety: UL power supply  
CE  
FCC  
RoHS

### WARRANTY

One year standard